

Maintenance-free Automotive Battery DIN SERIES

BULLS POWER Maintenance-free automotive battery DIN series has very good low temperature starting ability, super long shelf life and maintenance free under normal situation. Those batteries are manufactured under DIN technology standard, less electrolyte is consumed, good anti-vibration capacity. It's good used for car, tractor, mine-truck and the starting, lighting for the construction engineer vehicles.

GENERAL FEATURES

- High Capacity.
- Long life.
- High CCA and good starting performance.
- Good charging acceptance and vibration resistant performance.
- Application of advanced PE type separator.
- Application of TTP technology.
- Advanced sulfate-resistant technology.
- Advanced calcium lead alloy technology, maintenance-free design.
- Reliable labyrinth-like seal design.
- Lead alloy terminal apply heavy load.
- Full ranges models, good appearance and high standard design.



TYPICAL APPLICATIONS

- Starting, light and ignition for car, tractor, mine vehicle and mobile machinery shop.
- Starting and ignition for the diesel motor or gasoline motor
- Power for car, tractor, mine vehicle and mobile machinery shop.

SPECIFICATIONS >>

Type DIN	Dimensions(mm)			Capacity AH	DIN CCA	EN CCA	Dry Weight	Wet Weight	Terminal	Base Holddown
	L	W	H							
53520	197	128	227	35	150	240	7.60	11.10	3	
53653	208	175	175	36	175	300	8.50	12.30	1	B3/B4
53890	238	135	200	38	150	240	8.00	12.00	1	B9
54459	208	175	190	44	210	360	9.40	13.30	1	B3/B4
54519	242	175	175	45	220	360	9.30	13.30	1	B3/B4
54523	237	128	225	45	190	300	8.00	12.00	1	
54577	220	135	225	45	190	300	7.80	11.70	1	B1
55041	200	170	225	50	220	360	10.00	14.70	1	B3/B4
55056	242	175	175	50	320	540	11.00	15.00	1	B3/B4
55559	242	175	190	55	255	420	11.10	15.80	1	B3/B4
56048	272	175	225	60	170	280	12.40	17.80	1	B9
56068	230	170	210	60	240	390	12.00	16.40	1	
56073	242	175	190	60	280	480	12.00	16.20	1	B3/B4
56318	278	175	175	63	300	510	13.40	17.90	1	B3/B4
57024	272	175	225	70	315	540	14.20	19.30	1	B9
57113	278	175	175	71	400	680	14.50	19.00	1	B3/B4
58211	317	175	175	82		720	13.91	20.88	1	B3/B4
58513	302	172	215	85	320	540	16.00	23.70	1	B1
58821	353	175	190	88	395	640	17.10	23.70	1	B3/B4
59518	302	172	215	95	395	640	17.80	25.50	1	B1
60026	407	174	237	100	360	600	18.60	27.80	1	
60032	302	172	215	95	395	640	17.80	25.50	1	B1
60044	353	175	190	100	450	760	18.10	24.70	1	B3/B4
60527	345	175	239	105	410	16.60	25.10		1	
62033	513	189	223	120	420	680	20.50	32.55	1	B1
63530	513	189	223	135	420	680	22.35	34.70	1	
64020	513	189	223	140	460	760	22.35	34.70	1	
65513	513	223	223	155	540	900	24.72	40.19	1	
67018HD	513	223	223	170	600	1000	28.60	43.20	1	
68034	513	223	223	180	600	1000	28.60	43.20	1	
70027	518	276	242	200	630	1050	34.14	54.25	1	
72512	518	276	242	225	680	1150	36.90	58.30	1	
73011	518	276	242	230	540	900	36.90	58.30	1	